

Portable switchboard **RDS12SD** with holder

Switchboard with sockets in portable design with bracket for indoor and outdoor use on construction sites and in industrial areas with resistant cover against excessive heat and burning (hot wire test 650 °C).

- Dimensions **385x195x215mm** (h x w x d) with mechanical resistance of the enclosure: **IK08**
- Degree of protection: **IP44**
- Material: **ABS**
- Rated working voltage: **400VAC, 250VAC, 50Hz**
- Operating temperature: **-25°C to +55°C**



Select of typical version with RCD, sockets 250V SCHUKO						Sockets 250V 2P+T	Sockets 400V (A)		MCB characteristic B (A)			MCB characteristic C (A)		
Order code	Name	Assembly	MCB char.	InA (A)	Production key		16	32	1x16	3x16	3x32	1x16	3x16	3x32
004483475	EDS12SD RCD 4S/2 16/32/P B		B	32	EDS12SD RCD 4S/210/000/P	4	1	1	2	1				
004483476	EDS12SD RCD 4S/2 16/32/P B+C		B+C		EDS12SD RCD 4S/200/010/P	4	1	1	2				1	
004483477	EDS12SD RCD 4S/2 16/32/P C		C		EDS12SD RCD 4S/000/210/P	4	1	1				2	1	
004483478	EDS12SD RCD 6S/P B		B	16	EDS12SD RCD 6S/300/000/P	6			3					
004483479	EDS12SD RCD 6S/P C		C		EDS12SD RCD 6S/000/300/P	6						3		

Select of typical version with RCD, sockets 250V with ground pin						Sockets 250V 2P+T	Sockets 400V (A)		MCB characteristic B (A)			MCB characteristic C (A)			
Order code	Name	Assembly	MCB char.	InA (A)	Production key		16	32	1x16	3x16	3x32	1x16	3x16	3x32	
004483470	EDS12SD RCD 4/2 16/32/P B		B	32	EDS12SD RCD 4/210/000/P	4	1	1	2	1					
004483471	EDS12SD RCD 4/2 16/32/P B+C		B+C		EDS12SD RCD 4/200/010/P	4	1	1	2				1		
004483472	EDS12SD RCD 4/2 16/32/P C		C		EDS12SD RCD 4/000/210/P	4	1	1					2	1	
004483473	EDS12SD RCD 6/P B		B	16	EDS12SD RCD 6/300/000/P	6			3						
004483474	EDS12SD RCD 6/P C		C		EDS12SD RCD 6/000/300/P	6							3		